



Product Data Sheet
Model : 5MP 3K POE MOTORIZED ZOOM BULLET CAMERA, AUDIO-IN

System	Embedded RTOS design, dual core;32 bits DSP,pure hardware
Structure	compression, watch dog,16MB FLASH,128MB DDR3;
Sensor	5MP 1/2.7" CMOS,0.001Lux@F1.2(color),0Lux(IR ON);integrate IR-CUT drive, support linkage control between Sensor &IR-CUT& photosensitive& LED fill light, support day/night switch;Event: Motion Detection, Video Shelter
Video Process	H.265+/H.265/H.264 video coding, support dual stream, AVI format; code stream 500k~8M bps adjustable, support PAL and NTSC
Frame Rates	5MP and 4MP@25 FPS;3MP and below @30FPS
Image Output	Main stream:2880×1620,2592×1520,2560×1440,2048×1520,2304×1296,1920×1080;
	Sub stream:800×448,640×480,640×360,352×288;
Lens Specification	2.7 mm to 13.5 mm motorized varifocal lens,Field of View horizontal FOV: 95° to 26°, vertical FOV: 72° to 20°, diagonal FOV: 126° to 33°,Lens Mount: M12IR: 12milX4pcs SMD LED,IR Range: 40m, Smart IR: Support Shutter Time: Auto/Manual, 1/3~1/10000s Day/Night: IR cut filter with auto switch Wide Dynamic Range: DWDR Digital noise reduction: 2D/3D DNR Image Setting: Brightness/Contrast/Saturation/Hue/Sharpness BLC: Support - HLC: Support - ROI: Support - Defog: Support

Colourview Features	<p>"The Dual LED 5MP IP Color View Camera is a cutting-edge surveillance solution designed to deliver high-quality video footage with advanced features for enhanced security monitoring. With its 5-megapixel resolution and dual LED technology, this camera provides clear and vivid images, ensuring optimal visibility both day and night.</p> <p>"5MP Resolution: The camera boasts a 5-megapixel resolution, ensuring detailed and sharp images for effective surveillance and identification.</p> <p>Dual LED Technology: Equipped with dual LED technology, this camera enhances color reproduction in low-light conditions, providing clearer and more accurate video footage during nighttime surveillance."</p>
Audio Interface	<p>1channel input,support mic or pickup input;1channel output, support headset or amplifier play</p>
Audio code	<p>G.711 CODEC standard, support dual voice talkback, audio and video synchronization</p>
Network Interface	<p>1*RJ45 Ethernet interface,10/100M self-adaption,8KV anti-static electric capacity;support RTSP/DHCP/NTP,GB/T28181,compatible ONVIF and so on network protocols</p>
LED Passive Interface	<p>1* IR LED control output interface,1*IRCUT interface, support linkage control between IR-CUT and image.</p>
Business Functions	<p>Configure by WEB, OSD(on screen display),real-time video transmission, motion detection; support remote surveillance client software(Seetong); support mobile monitoring(Iphone, Android),support cloud service;</p>
Others	<p>DC12V power input interface,1.8W power consumption, front end power input, light protection,anti-static,anti-inverse connect, support 18V turn off voltage protection; size :38×38×11.1mm,8.9g,without housing PCBA,38 size single structure</p>
Work Conditions	<p>-40 ~+85</p>
Optional Functions	<p>E(POE cable power supply),Extended interface(Alarm IO, AUART_RX,Hard light-sensitive input ,PWM white light board , PWM infrared light board)</p>
General	<p>Metal Housing - Weather Proof: IP66 - Vandalproof: IK10 Dimensions: ϕ 284.5x 95.8(H) mm - Weight: 610g</p>