



## Product Data Sheet

Model : OPT-10-2STVR (Classic Series 10 Channel 4K NVR)

- Up to 10-Channel IP camera inputs
- H.265+/H.265/H.264+/H.264 video formats
- Video Output: 3840×2160,2560×1440,1920×1080
- 1 SATA interfaces for HDD connection (up to 14 TB capacity )



The most easy-to-use, popular and commercial 10 channel embedded NVR; specially design for store, small warehouse, office and family, access HD IPC, provide preview, recording, forward and so on functions. Support mobile phone monitoring, traversal service, achieve APP seconds connection for preview and remote recording playback, support various network modes:

- IPC----NVR---- Seetong Cloud----Seetong Client
- IPC-----NVR-----Seetong Client
- IPC----NVR---- Seetong Cloud----Seetong APP

System Structure	Embedded LINUX design,pure hardware decode,watchdog, hard disk storage,HDMI HD display,IP network video access.
Video Input	HD IPC access, each channel support dual stream access,support auto search,add,recording,preview and without debugging; Access bandwidth 64Mbps;
Video Output	1channel HDMI output,1 channel VGA output,homology with HDMI,support 3840×2160, 2560×1440,1920×1080,1440×900,1366×768,1280×1024,1280×800,1024×768 resolution output show; Support Seetong client preview,APP preview and seconds connection 1/2/4/6/8/9/10 pictures real time preview;
Video Recording Resolution	Support 720P/960P/1080P/3MP/4MP/5MP;
Video Capacity	Support H.265+/H.265/H.264 decoding; NVR local recording playback support 2CH (2*5MP); Seetong client recording playback support 2 channels.
Audio	Standard G.711, support audio and video recording,support HDMI output channel preview and playback audio and video, Seetong client audio and video preview and playback;
Storage	1*SATA hard disk interface,support 14TB capacity; Support schedule record, motion detection linkage record, alarm linkage record, cross-border record, regional invasion record, license plate record, human face record, human form record, vehicle form record;
User	Local maximum support for 38 users;
Network Interface	1*RJ45 Ethernet interface, support 10/100M self-adaption;support TCP/IP, IPv4, DHCP, NTP, RTSP, P2P, SMTP, GB28181 and so on protocols;
Peripheral Interface	2*USB2.0 interface(rear); support for the mouse, USB upgrade, import and export;
Front Panel	1* power,1*record,1*network indicator light;
Buzzer	Do not supported buzzer alarm;
Business Functions	Support preview/recording/forward/remote service, support alarm linkage, support Seetong client remote control software; support seetong cloud service;
Working Temperature	-10c~+55c
Working Humidity	10%~90%
Others	DC +12V/2A power input, hots power consumption≤2W (No disk), size 255*210*42mm (W*D*H), weight 566.7g, support wall hanging;
Extensible Interface	Expanded DC12V power input interface,Expanded USB interface, Expanded RJ45 Interface,Buzzer interface