



Product Data Sheet
Model : OPT-64-8STVR-AI
64 CHANNEL 4 SATA 4K AI NVR

The most easy-to-use, popular and commercial 64 channel embedded NVR; specially design for store, small warehouse, office and family, access HD IPC, provide preview, recording, forward and so on functions. Support mobile phone monitoring, traversal service, achieve APP seconds connection for preview and remote recording playback, support various network modes:

IPC----NVR---- Seetong Cloud----Seetong Client

IPC-----NVR-----Seetong Client

IPC----NVR---- Seetong Cloud----Seetong APP



Specification

8 Disk 64CH H.265+ NVR

Image Sensor

Embedded LINUX design,pure hardware decode,watchdog,hard disk storage,HDMI HD display,IP network video access.

Video Input

HD IPC access, each channel support dual stream access, support auto search,add,recording,

Preview and without debugging;

Access bandwidth 320Mbps;

Video Output

1 channel VGA output;support 1920×1080,1440×900,1366×768, 1280×1024,1280×800,1024×768 resolution output show;

2 channel HDMI output:

HDMI1 support 3840×2160,2560×1440,1920×1080,1440×900,1366×768,1280×1024,1280×800,1024×768 resolution output show;

HDMI2 homology with VGA,support 1920×1080,1440×900,1366×768,1280×1024,1280×800,1024×768 resolution output show;

When HDMI2 and VGA are connected at the same time, only HDMI2 output display;

Support Seetong client preview,APP preview and seconds connection

1/2/4/6/8/9/10/16/24/25/36/64 pictures real time preview;

Video recording resolution

Support 720P/960P/1080P/3MP/4MP/5MP/4K;

Video Capacity

Support H.265+/H.265/H.264 decoding;

NVR local recording playback support 4CH (4K@30fps) ;
Seetong client recording playback support 4 channels.

Audio

Supports a 4-pin 3.5mm audio input/output jack; Supports a 3.5mm audio input jack with 3pin pins;

Standard G.711, support audio and video recording,support HDMI output channel preview and playback audio and video, Seetong client audio and video preview and playback;

Storage	<p>8*SATA hard disk interface,support 18TB capacity;</p> <p>Support timing video recording, face, license plate, human shape, vehicle shape, high-altitude parabolic, motion detection, IO alarm linkage video recording;</p> <p>Support external USB storage devices (such as ordinary U disk, mobile hard disk) backup;</p>
User	Local maximum support for 38 users;
Network Interface	2*RJ45 Ethernet interface, support 10/100/1000M self-adaption; support TCP/IP, IPv4, DHCP, NTP, RTSP, P2P, SMTP, GB28181 and so on protocols;
Peripheral Interface	1*RS485 interface, support PELCO protocol rocker PTZ control keyboard;1*232 serial interface;1*USB3.0 interface;1*esata interface (supports USB2.0);support for the mouse, USB upgrade, import and export;
Alarm Interface	16 channel switch input, supporting alarm input;4-way relay output, supporting siren/alarm;
Front Panel	Support three status indicators of power supply, video recording and network;1*USB2.0 interface;
Business Functions	Support preview/recording/forward/remote service, support alarm linkage, support Seetong client remote control software; support seetong cloud service;
Working Temperature	-10 ~+55
Working Humidity	10%~90%
Weight and size	size 190.5*190.5*46mm (W*D*H), weight 5700g;
Others	AC 100~240V(50/60Hz) A TX power input;host power consumption<8W(Hard disk not included);Support lightning protection and anti-static;